

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 536700

PRIMARY CORNER DESCRIPTION C C for Secs. 34 & 35 only, T28-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5557)

Intersect S. bdy., 370 lks. S.89°18'W. of N. 1/4 Cor. Sec. 2, T29-3. Set Fir stake 3 ft. long, 4" sq., 24" in the ground for closing cor. secs. 34 and 35, marked C C T28S R3W on N.; S35 on E.; and S34 on W. face, with 2 grooves on E. and 4 grooves on W. face, from which
A Fir 6" dia., bears N.52°E., 20 lks. dist. mkd. T28S R3W S35 BT.
A Laurel 6" dia., bears N.48°W., 28 lks. dist. mkd. T28S R3W S34 BT.

Douglas Co. Surveyors Office - James Byron, Deputy, Milo Godfrey; Clete Putnam, crew - Feb. 2, 1960 - C.S. 49/47-11

Found - Orig. 6" now 20" Laurel N.48°W., 18.5 ft., shows good "28S R3W 34 CC" scribing.
No trace of orig. NE. BT found.
Set Brass cap at cor. mkd: County Surveyors Office
T 28 S R 3 W
S34 | S 35

T 29 S
1960
New BTs- 5" R.Fir bears N.16½°E., 24.3 ft. scribed S35 CSBT
15" R.Fir bears N.51°W., 22.5 ft. scribed T28S R3W
CC S34 CS BT.

Fd. OK by D. Edwards, Oct. 1999 - M133-43

Douglas Co. Surveyors Office - Stephen Flaue & Jeff Lorsung - 10/3/2018 - C.S. File 67/45-8

Found in good condition
9/17/2018 - C.S. FILE 67/45-25
NAD 83 N 526850.57 E 4245164.72
Lat: 43°05'03.3" Long: 123°01'52.9"W