TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6334)

Set Laurel post for the ¼ sec. cor., from which
A Laurel 5" dia., bears N.10°E., 15 lks. dist.
A Laurel 6" dia., bears S.14°E., 22 lks. dist.

Survey by Donald R. Martin - For: A. Kindred - Oct. 1960 - C.S. File 51/143

Proportionate measurement.
Set 1½" Iron pipe 36" long, 18" in ground and scribed two bearing trees:
12" Laurel N.45°E., 5.0 ft. scribed ¼ S26.
10" Fir S.37°W., 25.0 ft. scribed ¼ S35.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2157, Surveyed March/May 2007 - DCSO records Vol. 57 Pages 22554-5

Point for the ¼ sec. cor. of secs. 26 & 35, at proportionate dist.; there is no remaining evidence of the original cor.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T29S R3W ¼ S 26 / S 35 2007

from which
A fir, 17" dia., bears S.38½°W., 4.6 ft., mkd. ¼ S35 BT.
A fir, 18" dia., bears N.51¼°W., 50.1 ft., mkd. ¼ S26 BT.
Deposit magnet in a white plastic case at the base of the stainless steel post.
From this cor., a point established by Martin, in 1960, and is not accepted as the cor., bears S.88°34'43"W., 18.36 ft., monumented with an iron pipe, 2" dia., firmly set, projecting 16" above ground, with no cap, from which the remains of bearing trees mkd. by Martin
A tin capped sawed madrone stump, 17" dia., bears N.40¼°E., 4.3 ft., with fragmentary scribe marks visible on a partially healed blaze.
A decayed stump, size and species indeterminate, bears S.35¼°W., 26.4 ft., with no marks visible.