

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 540340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Timothy J. Moore & A. Bert Skeesick, Cadastral Surveyors under Group #2033, surveyed Sept. 2002/June 2003 (DCSO rec. Vol. 55 pg(s) 21332)

Point for the center ¼ sec. cor. of sec. 23, at intersection with the E. and W. centerline.

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T29S R3W

C 1/4
S 23
2003

from which

A fir, 13" dia., bears S.57°E., 23.8 ft., mkd. C¼ S23 BT.

A fir, 14" dia., bears S.27½°W., 15.7 ft., mkd. C¼ S23 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this point, an iron pipe, 1" dia. firmly set, projecting 2" above ground, bears N.41°38'08"E., 2.41 ft., established without authority during a 1979 BLM administrative survey. This monument is not accepted as the true cor. location and is removed and buried inside the stainless steel post.