

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page 6328)

Set Laurel post for the ¼ sec. cor., from which
A fir, 36" dia., bears N.3°E., 30 lks.
A fir, 36" dia., bears N.2°W., 44 lks.

BLM Dependent resurvey by Timothy J. Moore & A. Bert Skeesick, Cadastral Surveyors under Group #2033, surveyed Sept. 2002/June 2003 (DCSO rec. Vol. 55 pg(s) 21319)

The ¼ sec cor. of secs 35 & 36, determined from the orig. BTs
A fir, 53" dia. bears N.20½°E., 19.8 ft. with axe marks & fragmentary bark blaze, no scribe marks visible.
(Record, N.3°E.)
A fir, 39" dia., bears N.2°W., 29.0 ft., with axe and fragmentary scribe marks visible on bark blaze.

At the cor. point
Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, with brass cap mkd. T29S R3W
¼
S 35|S 36
2003

from which new bearing trees
A fir, 8" dia., bears S.62½°E., 40.5 ft., mkd. ¼ S36 BT.
A fir, 11" dia., bears S.65°W., 34.8 ft., mkd. ¼ S35 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description
Deposit a magnet in a white plastic case at the base of the stainless steel post.