

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6329)

Set Laurel post for the cor. to secs. 23, 24, 25 and 26, from which

- A Laurel 20" dia., bears N.50°E., 45 lks.
- A Laurel 14" dia., bears S.10°E., 32 lks.
- A Fir 40" dia., bears S.35°W., 23 lks.
- A Laurel 12" dia., bears N.72°W., 43 lks.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Oct. 29, 1957 - C.S. File 42/315-1

Determined by O.B.T.s

- 30" Laurel stump bears N.50°E., 29.7 ft.
- 44" Fir snag bears S.35°W., 15.2 ft.
- 10" Laurel bears N.64°W., 21.1 ft., found scribe. (should be N.72°W., 28.4 ft.)

At corner point, Set 1¼" x 24" Iron pipe, from which

- 9" Laurel bears N.64°W., 49.7 ft. mkd. S23 T29S BT.
- 6" Cedar bears N.48°W., 56.8 ft. mkd. S23 R3W BT.
- 10" Laurel bears N.29°W., 39.2 ft. mkd. S23 T29S R3W WM BT
- 9" Fir bears N.22°W., 22.9 ft. mkd. S23 BT.

BLM Dependent resurvey by Timothy J. Moore & A. Bert Skeesick, Cadastral Surveyors under Group #2033, surveyed Sept. 2002/June 2003 (DCSO rec. Vol. 55 pg(s) 21322-3)

The cor. of secs. 23, 24, 25, & 26, perpetuated by Markham, in 1957, from evidence of original BTs no longer in existence, monumented with an iron pipe, 1½" dia., firmly set, projecting 3" above ground, from which a BT mkd. by Markham

A cedar, 16" dia., bears N.49°W., 55.8 ft., with fragmentary scribe marks visible on a partially opened blaze.

At the cor. point

Set a stainless steel post, 28" long, 2" dia., 21" in the ground, with brass cap mkd.

T29S R3W
S 23 | S 24
S 26 | S 25
2003

from which new bearing trees

- A cedar, 15" dia., bears N.87½°E., 42.9 ft., mkd. T29S R3W S24 BT
 - A cedar, 20" dia., bears S.19¾°E., 95.3 ft., mkd. T29S R3W S25 BT.
- continued next page

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 19" dia., bears S.46 $\frac{3}{4}$ °W., 11.2 ft., mkd. T29S R3W S26 BT.
Deposit a magnet in a white plastic case at the base of and bury the iron pipe, 21" long, inside the stainless steel post
Each new bearing tree has a 2 $\frac{1}{2}$ "x $\frac{1}{4}$ " magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

Fd as per 2003 BLM visit, 6 ft. steel post is set 2 ft East, by D. Edwards, 3/2017 - M173-15