

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6330)

Set a Hemlock post for the ¼ sec. cor., from which
A Cedar 18" dia., bears S.26°E., 15 lks. dist.
A Hemlock 10" dia., bears N.80°W., 18 lks. dist.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. -
Wit: R.G. Boyd - Oct. 29, 1957 - C.S. File 42/315-10

Determined by old BTs:
24" Cedar bears S.25°E., 10.0 ft.
13" Hemlock bears N.79°W., 11.0 ft.
At corner point, Set 1¼" x 30" truck axle with spline up,
from which
10" Hemlock bears N.53°E., 20.5 ft. mkd. ¼ S24 BT.
15" Fir bears N.31°W., 26.5 ft. mkd. ¼ S23 BT.
Creek bears South 25.0 ft. Road bears South 85.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike
Darby; Wm. Stoffel, crew - Nov. 1962 - C.S. File 52/126-80

Found axle at corner and NW. BT, now down. NE. BT is dead.
New BTs- 12" Fir bears S.50°E., 87.0 ft. scribed ¼ S24 CS BT.
10" Hemlock bears S.1°W., 37.4 ft. scribed ¼ S23 CS
BT.

Mark Smalley - For: Roseburg Resources Co. - Oct. 1999 - M
134-8

Found - 1½" 16 spline axle.
24" Cedar S.25°E., 10.0 ft. stump, orig.
23" Hemlock S.1°W., 37.4 ft. healed
New BTs- 13" D.Fir S.76°E., 29.3 ft. "¼ S BT"
13" D.Fir N.20°E., 28.6 ft. "¼ S BT"
14" D.Fir N.29°W., 14.3 ft. "¼ S BT"

BLM Dependent resurvey by Timothy J. Moore & A. Bert
Skeesick, Cadastral Surveyors under Group #2033, surveyed
Sept. 2002/June 2003 (DCSO rec. Vol. 55 pg(s) 21323-4)

The ¼ sec. cor. of secs. 23 & 24, perpetuated by Markham, in
1957, further perpetuated by the Douglas Co Surveyors Office,
in 1962, & by Smalley, in 1999, monumented with a truck axle,
2¼" dia., firmly set, projecting 7" above ground, from which
the remains of an original BT

continued next page

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed cedar stump, 28" dia., bears S.26°E., 11.3 ft., with no marks visible. (Record, 9.9 ft.)

and a BT mkd. by the Douglas County Surveyors Office

A hemlock, 23" dia., bears S.1°E., 36.9 ft., with a healed blaze.

and bearing trees mkd. by Smalley

A fir, 14" dia., bears N.17¼°E., 28.5 ft., with scribe marks ¼ S BT visible on a partially healed blaze.

A fir, 14" dia., bears S.80¼°E., 28.8 ft., with scribe marks ¼ S BT visible on a partially healed blaze.

A fir, 16" dia., bears N.32°W., 14.2 ft., with fragmentary scribe marks visible on a partially healed blaze.

At the cor. point

Set a stainless steel post, 28" long, 2½" dia., 20" in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T29S R3W

¼

S 23 | S 24

2003

Deposit a magnet in a white plastic case at the base of and bury the axle, 24 ins. long, inside the stainless steel post. Each new bearing tree has a 2½" x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description