

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6330)

Set Hemlock post for the cor. to secs. 13, 14, 23 and 24, from which

- A Fir 50" dia., bears N.89°E., 23 lks. dist.
- A Fir 60" dia., bears S.58°E., 38 lks. dist.
- A Fir 10" dia., bears S.70°W., 40 lks. dist.
- A Fir 16" dia., bears N.42°W., 44 lks. dist.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Oct. 29., 1957 - C.S. File 42/315-5

Determined by O.B.T.s:

- 70" Fir snag bears S.58°E., 25.0 ft., found scribe.
- Stump hole bears N.89°E., 15.1 ft.

At corner point, Set truck axle with flange up, from which

- 20" Alder bears S.54°W., 37.6 ft. mkd. S23 T29S R3W BT.
- 10" Maple bears N.79°W., 20.8 ft. mkd. S14 BT.
- 15" Hemlock bears S.86°W., 33.0 ft. mkd. S23 BT.
- 10" Fir bears S.85°E., 42.3 ft. mkd. S24 BT.
- 12" Fir bears N.87°E., 35.0 ft. mkd. S13 BT.

Creek bears South, 60 ft. Road bears East 180 ft.

BLM resurvey by James J. Carlson, Cadastral Surveyor, under Group #892, surveyed June/July 1976 - (DCSO records Vol. 39 Page(s) 15847-48)

The Sec. cor., perpetuated by Markham in 1957, monumented with a truck axle 1" dia., firmly set, projecting 6" above ground, with 4" flange, from which the remains of the original bearing trees:

- A root crown bears N.89°E., 23 lks. dist.
- A root hole bears S.58°E., 38 lks. dist. with a down Fir alongside 70" dia., with fragmentary scribe marks visible on bark.

and bearing trees mkd. by Markham:

- A Fir 20" dia., bears N.87°E., 55 lks. dist. with healed double blaze.
- A Fir 13" dia., bears S.85°E., 65 lks. dist., with healed double blaze.
- An Alder 15" dia., bears S.51°W., 58 lks. dist., with fragmentary scribe marks visible on open blaze.
- A Hemlock 23" dia., bears S.86°W., 50 lks. dist., with healed double blaze.

(Cont. Next Page)

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Maple 15" dia., bears N.79°W., 32 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 29 S R 3 W
S 14 | S 13
S 23 | S 24
1976

Deposit axle alongside iron post.

BLM Dependent resurvey by Timothy J. Moore & A. Bert Skeesick, Cadastral Surveyors under Group #2033, surveyed Sept. 2002/June 2003 (DCSO rec. Vol. 55 pg(s) 21324-5)

The cor. of secs. 13, 14, 23, & 24, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree

A roothole, bears S.58°E., 25.1 ft., with fallen fir trunk, 36" dia., lying alongside, with no marks visible.

and the remains of BTs mkd. by Markham, reported by Carlson

A fir, 31" dia., bears N.87°E., 36.3 ft., with healed double blaze.

A fir, 17" dia., bears S.85°E., 42.9 ft., with healed double blaze.

An alder snag, 15" dia., bears S.51°W., 38.3 ft., with healed double blaze.

A hemlock, 28" dia., bears S.86°W., 33.0 ft., with healed double blaze.

A maple, 15" dia., bears N.79°W., 21.1 ft., with healed double blaze.

and a new bearing tree

A hemlock, 10" dia., bears S.62¼°W., 44.0 ft., mkd. T29S R3W S23 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

(NAD 1983 (CORS))

Latitude: 43°02'27.96"N

Longitude: 123°01'16.77"W