

PRIMARY CORNER DESCRIPTION Sec Cor for 1, 2, 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6332)

Set Fir post for the cor. to secs. 1, 2, 11 and 12, from which

- A Fir 48" dia., bears N.80°E., 46 lks. dist.
- A Laurel 8" dia., bears S.6°E., 60 lks. dist.
- A Fir 6" dia., bears S.35°W., 46 lks. dist.
- A Fir 10" dia., bears N.50°W., 43 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell; Wm. Stoffel, crew - Oct. 1962 - C.S. File 52/126-67

Found - Orig. 10" now 37" Fir stump, N.50°W., 28.4 ft. We open and find good scribing "2".
Orig. now 48" Fir N.80°E., 30.4 ft., no scribing found.

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S R 3 W
S 2 | S 1
S11 | S12
1962

New BTs- 20" Fir bears N.12°W., 16.7 ft. "S2 T29S R3W CS BT."
Rescribe (bark) 44" Fir N.83°E., 28.4 ft. "S1 T29S R3W CS BT"
14" R.Fir bears S.35°E., 19.3 ft. "S12 T29S R3W CS BT"
12" R.Fir bears S.87°W., 30.0 ft. "S11 T29S R3W CS BT".

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13804)

The Sec. Cor., remonumented and recorded by Byron in 1962, with an iron post 1" dia., 6" above the ground with brass cap mkd. in 1962

from which the remaining original bearing trees:

- A Fir 54" dia., bears N.85°E., 46 lks. dist., no original marks remaining. Remarked "T29S R3W S1 CS BT" on bark blaze by Byron. (Rec. N.80°E.)
- A sawed Fir stump 36" dia., bears N.50°W., 45 lks. dist., 43 lks. to face, with scribe mark 2 on an opened blaze. (Rec. 43 lks.)

and bearing trees mkd. by Byron:

(Cont. Next Page)

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec Cor for 1, 2, 11 and 12

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A Fir 13" dia., bears S.32½°E., 29½ lks. dist., with a partially healed double blaze.
A Fir 11" dia., bears S.86°W., 46 lks. dist., with a partially healed double blaze.
A Fir 21" dia., bears N.12°W., 25 lks. dist., with a partially healed double blaze.
Add the marks BLM to the brass cap.

FD. Ok by Tony Hostetter 4/2006 - M150-38
Fd. OK by D. Edwards, June 2007 - M153-49