

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6324-25)

-----

Set Yew post for cor. to secs. 1, 2, 35 and 36, from which

- A Maple 15" dia., bears N.14°E., 24 lks.
- A Maple 16" dia., bears S.42°E., 6 lks.
- A Maple 16" dia., bears S.48°W., 22 lks.
- A Fir 12" dia., bears N.23°W., 31 lks.

GLO resurvey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5548)

-----

Cor. secs. 1, 2, 35 and 36, which is a stake marked and witnessed as described by the Surveyor General. I destroy markings on this cor. referring to secs. 35 and 36.

BLM resurvey by James J. Carlson, Cadastral Surveyor, under Group #892, surveyed June/July 1976 - (DCSO records Vol. 39 Page(s) 15845)

-----

(37.16 chs.)

Point selected for the witness cor. to the cor. of secs. 1 and 2 only.

Set an iron post 28" long, 2½" dia., 20" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

W C

T 28 S R 3 W

← S 35

---

S 2 | S 1

T 29 S R 3 W

1976

from which

- A Fir 5" dia., bears S.17°E., 46½ lks. dist., mkd. X BT
- An Alder 10" dia., bears S.25°W., 196½ lks. dist. mkd. X BT on bark.

(37.86 chs. N.89°29'W)

Point for the cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner. The corner point is located in South Myrtle Creek, 12 lks. wide, course S.60°W., where it is impracticable to establish a permanent monument.

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyor's Office - Crew: Stephen J Flause & Jeffery Lorsung - 10/8/2018 - C.S. File 67/45-23

-----  
Found - A 2" i.d iron pipe by Carlson USBLM Cadastral Surveyor, in 1976, firmly set, projecting 4" above ground in a 18" dia. stone collar with a 3/4" dia. brass cap (properly) mkd.

The monument is a Witness Corner, the true corner position bears N.89°29'W., 0.70 Chains per a 1976 USBLM Dependent Resurvey.

BTs by Carlson 1976:

A 18" dia. D.Fir bears S.17°E., 30.7 ft. with healed double blaze

A 16" dia. Alder bears S.25°W., 128.6 ft. with healed double blaze (Rec. 196.5 lks. = 129.7 ft.)

New BTs- A 14" D.Fir bears S.54°W., 21.9 ft. scribed "T29S R3W S2", "CS BT" on a double blaze.

LOCATION & COMMENTS -

The corner falls in South Myrtle Creek. The witness Corner is South 20 ft from the center of the creek. All new BTs are double blazed and tagged No trees were marked to the North due to the creek and thick riparian zone.

GEODETIC COORDINATES

N 526,770.79 E 4,247,964.91

LATITUDE: 43°05'03.383"N. LONGITUDE: 123°01'15.117"W.

DATUM: NAD 83, Epoch 2010.00 SOURCE: Trimble GeoXT 6000

COMPASS DECLINATION: 15°E.