

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 13

Alias	Description

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1383, Surveyed May/June 1987 - (DCSO records Vol. 48 Page(s) 18377)

Point for the center ¼ sec. cor. of sec. 13, at intersection with the E. and W. center line.
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T 29 S R 3 W
C¼ S 13
1987

from which
A Yew 19" dia., bears N.12°E., 75 lks. dist., mkd. C¼ S13 BT.
An Alder 10" dia., bears S.3°E., 29 lks. dist., bark scribed C¼ S13 BT.
Deposit white "DEEP-1" magnetic marker at base of stainless steel post. Alongside the corner is a steel fence post of unknown origin, firmly set.

Ronald L. Rice, Ward NW - April 2009 - M 159-14

Found - 3¼" BLM brass cap dated 1987
Rec. 19" Yew bearing N.12°E., 49.5', down, out of position.
10" Alder bears S.3°E., 19.1', bark scribing visible
New BT - 28" D.Fir bears N.41°E., 36.8', blazed, scribed "C¼ S13 BT"