

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6331-32)

Set a Laurel post for the 1/4 sec. cor., from which
A Laurel 8" dia., bears N.35°E., 16 lks. dist.
A Laurel 10" dia., bears S.56°W., 12 lks. dist.

Survey by Claude Kerr - June 6, 1950 - C.S. File 40/252

Found iron markings, but markings nearly all gone.
I reset corner from the original BT. Set a 4" x 4 ft. Cedar post at corner and remarked the original BT with "1/4 S BT", a 10" Laurel, N.35°E., 16 lks.
New BTs- 12" Fir bears N.50°E., 18 lks. mkd. 1/4 BT.
10" Laurel bears S.30°E., 9 lks. mkd. 1/4 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Nov. 1962 - C.S. File 52/126-80

Found - Orig. BT, N.35°E., 10.6 ft., showing good reverse scribing.
Stake at cor. and both BTs as recorded by Kerr, except 12" now 13" Fir should be N.50°W., 11.9 ft. not N.50°E., 11.9 ft.
Orig. NE. BT, has been rescribed in bark "1/4 S BT".
Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 3 W
1/4 S 12
S 13
1962

No new bearing trees scribed.
Corner is on West slope and 150 ft. West of top of ridge.

BLM resurvey by James J. Carlson, Cadastral Surveyor, under Group #892, surveyed June/July 1976 - (DCSO records Vol. 39 Page(s) 15851)

The 1/4 sec. cor., perpetuated and recorded by Kerr in 1960, further perpetuated and recorded by Byron in 1962, monumented with an iron post, 1 1/2" dia., firmly set, projecting 10" above ground, with 1962 brass cap, from which the remains of the original bearing trees:
A Madrone 14" dia., bears N.30 1/2°E., 16 lks. dist., with healed blaze. This tree was remarked 1/4 S BT on bark, by Kerr, in 1960.

(Cont. Next Page)

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Madrone stump 15" dia., bears S.56°W., 12 lks. dist., no marks visible.
and the remains of bearing trees mkd. by Kerr
A sawed Fir stump 15" dia., bears N.50°W., 18 lks. dist., with healed blaze.
A sawed Madrone stump 11" dia., bears S.18°E., 9 lks. dist., with healed blaze.
and a new bearing tree
A Cedar 15" dia., bears S.19°W., 25 lks. dist., mkd. ¼ S13 BT.

Fd. and used in BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1383, Surveyed May/June 1987 - (DCSO records Vol. 48 Page(s) 18378)

FD. Ok by Tony Hostetter 4/2006 - M150-38