

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 641700

PRIMARY CORNER DESCRIPTION C C for Secs. 35 & 36, T28-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 resurvey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5552)

-----  
At a point 96 lks. W. from N. 1/4 Cor. Sec. 1, T29S R3W, Set granite stone 6x8x12 ins., 8" in the ground for closing cor. secs. 35 and 36, marked C C on N. face, with 1 groove on E. and 5 grooves on W. face, from which  
A Fir 30" dia., bears N.67°E., 45 lks. dist. mkd. T28S R3W S36 BT.  
A Laurel 8" dia., bears N.26°W., 38 lks. dist. mkd. T28S R3W S35 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Feb. 2, 1960 - C.S. 49/47-10

-----  
Found - Orig. 8" now 20" Laurel N.26°W., 25.1 ft. shows good scribing on old face.  
Orig. NE. BT, face down in pond.  
Corner in pond. I do not set brass cap. North ¼ cor. for sec. 1, T29S R3W bears S.84°E., 58.0 ft.  
New BTs- 12" R.Fir N.33°W., 21.6 ft. scribed CC S35 T28S R3W CS BT.  
7" R.Fir bears N.2°E., 38.2 ft. scribed CC S36 T28S R3W CS BT.

Douglas Co. Surveyors Office - John M. Powell and crew - Dec. 22, 1966 - C.S. File 52/126-149

-----  
Found - 12" now 14" R.Fir N.33°W., 21.6 ft., alive, blazes healed.  
7" now 10" R.Fir N.2°E., 38.2 ft., alive, blazes healed.  
Orig. Laurel N.26°W., 25.1 ft., alive, scribe visible on decaying face.  
Corner falls in pond 60 ft. in dia. and approx. 5 ft. deep.  
Set Witness Cor. 30 ft. North of true corner.  
Set brass cap at cor. mkd: County Surveyors Office  
T 28 S R 3 W  
CC S 35 | S 36  
Wit. Cor T 29 S R 3 W  
30 ft. S. to corner  
1966  
Rescribe 10" R.Fir N.3°E., 8.2 ft., added "WC" between blazes.  
New BT - 9" R.Fir N.70°W., 9.1 ft. mkd. "WC T28S R3W S35 CC CS BT."  
Witness corner lies 7 ft. N. of edge of pond.

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 641700

PRIMARY CORNER DESCRIPTION C C for Secs. 35 & 36, T28-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by James J. Carlson, Cadastral Surveyor, under Group #892, surveyed June/July 1976 - (DCSO records Vol. 39 Page(s) 15844)

-----  
(Corner Report Only)

The closing cor. of secs. 35 and 36, perpetuated and recorded by Byron in 1960, from which the remains of the original bearing trees:

A Madrone 18" dia., bears N.26°W., 38 lks. dist., with fragmentary scribe marks visible on open blaze.

and bearing trees mkd. by Byron:

A Fir 11" dia., bears N.2°E., 58 lks. dist., with healed double blaze. This tree was remarked by Tracy, in 1966.

A Fir 15" dia., bears N.33°W., 33 lks. dist., with healed double blaze.

Corner is located in a pond, 1 ch. dia.

From the corner point, a witness corner established by Tracy in 1966, bears North 45½ lks. dist., monumented with an iron post, 1" dia., firmly set, projecting 10" above ground, with brass cap mkd. in 1966, from which bearing trees mkd. by Tracy

A Fir 11" dia., bears N.3°E., 12½ lks. dist., with healed blaze.

A Fir 10" dia., bears N.70°W., 15 lks. dist., with fragmentary scribe marks visible on open blaze.