

PRIMARY CORNER DESCRIPTION Cor. to secs. 30 & 31 only, T29-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6224-25)

Set an iron post 3 ft. long, 2' dia., 24" in the ground for cor. of secs. 30 and 31, with brass cap marked

T29S
S30
S31
R2W
1917

from which

A Fir 28" dia., bears N.16°15'E., 78 lks. dist. mkd. T29S R2W S30 BT.

A Fir 38" dia., bears S.16°30'E., 161 lks. dist. mkd. T29S R2W S31 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Dec. 1962 - C.S. File 52/136-95

Found - Brass cap at corner and both BTs., show scars.
New BTs- 13" Laurel bears N.47°E., 29.9 ft. scribed S30 T29S R2W CS BT.
12" R.Fir bears S.46°E., 34.0 ft. scribed S31 T29S R2W CS BT.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2157, Surveyed March/May 2007 - DCSO records Vol. 57 Page(s) 22550

The cor. of secs 30 & 31 only, T29S R2W perpetuated by Byron, in 1963, bears S.0°58'00"E., 185.78 ft. monumented with an iron post, 2" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd.

from which bearing trees mkd. by Strickler

A fir, 37" dia., bears N.7¼°E., 49.2 ft., with a healed blaze. (Record; N.16¼°E., 51.5 ft.)

A fir, 47" dia., bears S.25½°E., 99.9 ft., with a healed blaze. (Record; S.16½°E., 106.3 ft.)

and the remains of bearing trees mkd. by Byron

A madrone, 14" dia., bears N.46¼°E., 30.0 ft., with a healed blaze.

A fir, 20" dia., bears S.47°E., 33.4 ft., with a healed blaze.