

PRIMARY CORNER DESCRIPTION Sec Cor for 24 & 25 only (East)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page 6321)

-----  
Set Fir post for cor. to secs. 19, 24, 25 and 30, from which  
A Chinquapin 8" dia., bears N.15°E., 12 lks.  
A Laurel 10" dia., bears S.55°E., 80 lks.  
A Cedar 14" dia., bears S.10°W., 13 lks.  
A Fir 18" dia., bears N.18°W., 46 lks.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6226)

-----  
Intersect the point for old cor. of secs. 19, 24, 25 and 30, established by references to the SW. and NW. bearing trees as described by the surveyor general; all other traces of the cor. have disappeared. I change this cor. to refer to secs. 24 and 25 only and perpetuate it as follows; at the exact cor. point  
Set a basalt stone, 15x10x8 ins., 10" in the ground, marked with 2 notches on S. and 4 notches on N. edge; from which  
A Cedar 18" dia., bears S.10°W., 13 lks. dist. mkd. T29S R3W S25 BT.  
A Fir 24" dia., bears N.18°W., 46 lks. dist. mkd. T29S R3W S24 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Dec. 1962 - C.S. File 52/126-92

-----  
Found stone at corner and both BTs as recorded.  
Set brass cap alongside corner stone, mkd:  
County Surveyors office  
S24 | T29S  
R3W S25 | R2W  
1962  
The corner is on steep South slope.

Fd. by Mark Smalley - Oct. 1999 - M 134-8

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2157, Surveyed March/May 2007 - DCSO records Vol. 57 Pages 22551-2

-----  
The cor. of secs 24 & 25 only, on the E. bdy. of the Tp., perpetuated by Byron, in 1962, monumented with an iron post, 1¼" dia., firmly set, projecting 16" above ground, with the original stone, 12x12x9", lying alongside, with 5 grooves visible, and a brass cap (properly) mkd. cont.

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which bearing trees mkd. by Strickler  
A cedar, 42" dia., bears S.10°W., 8.6 ft., with a healed blaze.  
A fir, 34" dia., bears N.18°W., 28.6 ft., with a healed blaze. (Record, 30.4 ft.)