

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6322)

Set Fir post for ¼ sec. cor., from which
A Fir 36" dia., bears N.75°E., 23 lks.
A Fir 30" dia., bears N.70°W., 26 lks.

GL0 resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6226)

Intersect the old ¼ sec. cor., which is a badly decayed post, firmly set in the ground, witnessed as described by the surveyor general. I change this cor. to refer to sec. 24 only and perpetuate it as follows: alongside the old cor. Set a basalt stone 15x10x8 ins., 10" in the ground for ¼ cor. of sec. 24 only, marked ¼ on W. face; from which
A Fir 32" dia., bears S.34°15'W., 52 lks. dist. mkd. ¼ S24 BT. (New BT)
A Fir 30" dia., bears N.70°W., 26 lks. dist., mkd. ¼ S24 BT. (Old BT)

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Oct. 29, 1957 - C.S. File 42/315-4

Determined by O.B.T.s
30" Fir bears N.69°W., 18.0 ft., found scribe.
26" Fir bears S.33°W., 33.3 ft.
At corner point, found stone and set 1¼" x 24" Iron pipe, from which
26" Fir bears S.64°E., 41.0 ft. mkd. ¼ S24 BT.
12" Fir bears N.82°E., 30.5 ft. mkd. ¼ S24 BT.
Section corner for 19 & 30, T29S R2W, brass cap bears North 16.0 ft.
Main top and road bears North 585.0 ft.

Fd. OK, July 1973, V. Tracy, DCSO - RESET STONE - C.S. File 56/34-19

BLM resurvey by James J. Carlson, Cadastral Surveyor, under Group #892, surveyed June/July 1976 - (DCSO records Vol. 39 Page(s) 15836)

The ¼ sec. cor., perpetuated and recorded by Markham in 1951, monumented with the original basalt stone 15x10x8 ins., lying on top of ground, mkd. ¼ on W. face, alongside of which is an (Cont. Next Page)

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

iron pipe, 1½" dia., firmly set, projecting 4" above ground, from which the remains of the original bearing trees:

A sawed Fir stump 40" dia., bears N.70°W., 26 lks. dist., with axe marks visible.

and the remains of bearing trees mkd. by Strickler:

A sawed Fir stump 27" dia., bears S.34¼°W., 52 lks. dist., with axe marks visible.

and the remains of bearing trees mkd. by Markham:

A sawed Fir stump 36" dia., bears S.66°E., 59 lks. dist., no marks visible.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 29 S
R 3 W | R 2 W
¼ S 24 |
1976

from which new bearing trees:

A Fir 7" dia., bears S.26°W., 134 lks. dist., mkd. ¼ S24 BT.

A Fir 8" dia., bears N.63¼°W., 113 lks. dist., mkd. ¼ S24 BT.

Insert Iron pipe inside iron post and deposit corner stone alongside iron post.

Fd. by Mark Smalley - Oct. 1999 - M 134-8