

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 700401

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 19 only, T29-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6227-28)

Set an Iron post 3 ft. long, 1" dia., 26" in the ground for ¼ cor. of sec. 19 only, with brass cap mkd: ¼
S19
1917

from which
A Fir 40" dia., bears N.77°E., 93 lks. dist. mkd. ¼ S19
BT.
No other bearing tree available; raise a mound of stone 2 ft. base, 1½ ft. high, E. of cor.

BLM resurvey by James J. Carlson, Cadastral Surveyor, under Group #892, surveyed June/July 1976 - (DCSO records Vol. 39 Page(s) 15838)

The ¼ sec. cor. of sec. 19 only, monumented with an iron post 1" dia., firmly set, projecting 10" above ground with brass cap as mkd. in 1917

from which the original bearing tree
A Fir 45" dia., bears N.77°E., 93 lks. dist., with healed blaze.
and a new bearing tree
A Fir 15" dia., bears S.64½°E., 95 lks. dist. mkd. ¼ S19
BT.