

TOWNSHIP 29 RANGE 04E POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Cor Secs 19, 30; 24, & 25 T29-3E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,  
under special instructions dated Dec. 27, 1920, Surveyed  
June/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10788)

-----  
Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for  
cor. of secs. 19, 24, 25, & 30, with brass cap mkd

T 29 S  
R 3 E R 4 E  
S 24 | S 19  
S 25 | S 30  
1927

from which

- A fir, 8" dia., bears N.86°E., 58 lks., mkd: T29S R4E S19  
BT.
- A fir, 24" dia., bears S.48°E., 86 lks., mkd: T29S R4E S30  
BT.
- A fir, 20" dia., bears S.17°W., 114 lks., mkd: T29S R3E  
S25 BT.
- A fir, 20" dia., bears N.89°W., 69 lks., mkd: T29S R3E S24  
BT.