

TOWNSHIP 29 RANGE 04E POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW Township corner

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed June/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10793)

Set an iron post, 3 ft. long, 3" in dia., 10" in the ground to bed rock, and build a mound of stone, 4½ ft. base, 2 ft. high, around the post, for cor. of Tps. 28 & 29S, R 3 & 4 E, with brass cap marked

T 28 S
R 3 E R 4 E
S 36 | S 31
S 1 | S 6
1927

from which

- A hemlock, 20" dia., bears N.78°E., 93 lks., mkd: T28S R4E S31 BT.
- A fir, 22" dia., bears S.57°E., 195 lks., mkd: T29S R4E S6 BT.
- A fir, 12" dia., bears S.34°W., 149 lks., mkd: T29S R3E S1 BT.
- A pine, 15" dia., bears N.41°W., 28 lks., mkd: T28S R3E S36 BT.