

PRIMARY CORNER DESCRIPTION Cor. Secs. 31, 32; 5, & 6 T30-4E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Herbert N Raymond, US Cadastral Engineer, Under Special Instr. dated Aug. 24, 1928, Group No. 133; surveyed Oct. 1928/July 1929 - (DCSO records C.S. File 65/87-42C&D)

-----  
 Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 5, 6, 31, & 32, with brass cap mkd:

T29S R4E  
 S 31|S 32  
 S 6|S 5  
 T30S  
 1929

from which

A hemlock, 16" dia., bears N.59½°E., 98 lks., mkd: T29S R4E S32 BT.

A pine, 28" dia., bears S.11½°E., 115 lks., mkd: T30S R4E S5 BT.

A fir, 48" dia., bears S.75°W., 24 lks mkd: T30S R4E S6 BT

A fir, 36" dia. bears N.32°W., 48 lks mkd: T29S R4E S31 BT

Jackson Co. Surveyors Office, Edward McGinty, Co. Surveyor - R. Roberts & E. Graham - Sept. 12, 1977 - C.S. File 65/87-39

-----  
 Found - The iron post, 28" below the asphalt road, with 2½" dia. brass cap marked as recorded in 1929. Directly above this monument I set a 1x12" G.I. pipe over a 5/8x16" iron pin, both slightly below the road surface, and a 2½" brass cap flush with the surface marked: Jackson County 1977

T29S  
 R4E  
 S31|S32  
 S 6|S 5  
 T30S

from which the orig. BTs were fd. as follows, measuring to center of tree at bottom of the single blaze:

White pine, 30" dia bears S.7½°E., 75.7 ft. Record; S.11½°E., 75.5 ft.

Hemlock 24" dia brs N.59½°E. 74.7 ft Rec N.59½°E., 64.7 ft Both trees have scribing visible in partially healed blaze. A k-tag on a 24" dia. fir which bears N.14°E., 39.2 ft. reads: "GWK 1956, S.15°W., 37.0 ft. to corner. 18" deep."

I marked the following trees "CS "BT" & took measurements to center of tree at the lower blaze:

White pine 17" dia. bears S.68°W., 65.7 ft.

White fir, 20" dia., brs. N.14½°W., 71.9 ft.

I also set four nail and shiner straddles at 2.00 ft. (0.61 M.) in approximate cardinal directions from the corner.

V = 19°