

TOWNSHIP 29 RANGE 04E POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION WC 1/4 Secs. 32; & 5 T30-4E

Alias 241100 Description PLSS for Witness corner  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, US Cadastral Engineer, Under Special Instr. dated Aug. 24, 1928, Group No. 133; surveyed Oct. 1928/July 1929 - (DCSO records C.S. File 65/87-42D)

-----  
East bet. secs. 5 & 32 @ 40.00 chains  
Point for ¼ sec. cor. fall in highway.  
At 40.25 chains  
Set an iron post, 3 ft. long, 1" dia., 30" in the ground, witness cor. to ¼ sec. cor., with brass cap marked

W C  
¼ S 32  
S 5  
1929

from which

A pine, 18" dia., bears N.83°E., 11 lks. mkd: W C ¼ S32 BT  
A pine, 16" dia., bears S.57°E., 48 lks., mkd: W C ¼ S5 BT

Jackson Co. Surveyors Office, Edward McGinty, Co. Surveyor - R. Roberts & H Center, USFS - Oct. 15, 1976 - C.S. File 65/87-40

-----  
From the following evidence:  
Set a 1x36" G.I. pipe, flush, with 2½" bronze disc mkd:  
Jackson County 1976

T295  
¼ S32 WC  
S 5  
T305  
R4E

from which

The original BT, 30" Pine with "WC ¼ S32 B" scribe visible bears record N.83°E., 7.3 ft. to center of tree.  
D.Fir, 21" dia., recently mkd. "¼ S5 RBT" in lower blaze by USFS, and which I mkd. "CS" in upper blaze, bears S.69°W., 73.8 ft. to center of tree at lower blaze.  
P.Pine, 16" dia., which I mkd. "CS""BT" bears N.21°E., 51.2 ft. to center of tree at lower blaze.  
The witness corner lies about 30 ft. West of the centerline of Road No. 3025 and 150 ft. North of a creek.  
V=19½°

Jackson Co. Surveyors Office, Roger R. Roberts, Co. Surveyor - H. Durkee & B. Beeman - July 25, 2007 - C.S. File 65/87-40

-----  
Found - At the corner position, flush, the 1" dia., galv. iron pipe with a 2½" dia., brass cap set on 1976 re-establishment in 1976 (properly) mkd.  
continued next page

TOWNSHIP 29 RANGE 04E POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION WC 1/4 Secs. 32; & 5 T30-4E

Alias 241100 Description PLSS for Witness corner

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Single remaining orig. BT recorded by Raymond of the GLO in 1928, A Fir snag with an opened single blaze revealing scribe marks "WC ¼ S 32B" brs. record; S.83°E., 7.3 ft. to center at base.  
A USFS BT, A D.Fir, now 33" dia., with a healed single blaze brs. record; S.69°W., 73.8 ft. to center at base.  
BT recorded on 1<sup>st</sup> re-establishment in 1976, a P.Pine, now 20" dia., with healed double blazes brs. N.23°E., 51.2 ft. Rec. N.21°(typed as it appears on orig.) to center at lower blaze.  
Mark new BTs "CS" "BT" and take measurement to center of trees at lower blaze:  
Lodgepole pine 7" dia., brs. N.10°W., 17.5 ft.  
Lodgepole pine 11" dia., brs. S.19°E., 58.2 ft.  
Corner lies approx. 30 ft. west of gravel road and approx. 150 ft. north of Crater Creek.  
V=19°15'