


TOWNSHIP 29 RANGE 04E POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records Vol. 26 page(s) 10926-7)

Set an iron post, 3 ft. long, 1" dia., 30" in the ground, for 1/4 sec. cor., with brass cap marked



from which

- A pine, 12" dia., bears S.83½°E., 60 lks., mkd: 1/4 S28 BT.
- A fir, 34" dia., bears S.69°W., 69 lks., mkd: 1/4 S29 BT.

Harold Carter - For: Rogue River Nat'l Park - 8/1979 - C.S. File 58/176-9 (second pg)

At the corner location I found the following reference:

- A 45" dia. D.Fir with a healed single blaze.
- No evidence of the orig. 12" pine could be found.
- At record bearing and distance I found the orig. GLO monument in good condition but buried 10" under a mound of earth.

From which I established the following reference,

- A 22" in dia. Fir bears N.31°30'E., 247 lks. Scribed 1/4 S28 LS 1071 BT on a double blaze.