

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records Vol. 26 page(s) 10927)

-----  
Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 20, 21, 28, & 29, with brass cap mkd:

T29S	R4E
S 20	S 21
S 29	S 28
1930	

from which

- A pine, 12" dia., bears N.9°E., 104 lks., mkd: T29S R4E S21 BT.
- A fir, 15" dia., bears S.16°E., 45 lks., mkd: T29S R4E S28 BT.
- A fir, 9" dia., bears S.5½°W., 50 lks., mkd: T29S R4E S29 BT.
- A fir, 17" dia., bears N.76°W., 24 lks., mkd: T29S R4E S20 BT.

Harold Carter - For: Rogue River Nat'l Park - 8/1979 - C.S. File 58/176-9 (both pages)

-----  
At the corner location I found the following references:

- A 19" dia. pine stump bears N.8°E., 104 lks. Scribed P on stump and 29S R4E S21 B on log lying along side, in a single blaze.
- A 23" dia. fir bears S.20°E, 45 lks with a single healed blaze.
- A 11" dia. fir snag bears S.4°W., 50 lks, illegible scribing visible on single blaze (face has been scraped by a cat).
- A 20" dia. fir bears N.76°W., 24 lks with a healed single blaze.

From which I fd the orig. monument lying 6" underground and tipped at about a 40 degree angle. I reset this monument at record distances and established the following new references:

- A 12" dia. pine bears North 107 lks. Scribed T29S R4E S21 LS 1071 BT on a double blaze.
- A 8" dia. fir bears S.44°30'W., 35 lks. Scribed T29S R4E S29 LS 1071 BT on a double blaze.