

TOWNSHIP 29 RANGE 04E POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records Vol. 26 page(s) 10933-4)

-----  
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 4, 5, 8, & 9, with brass cap mkd:

T29S	R4E
S 5	S 4
S 8	S 9
1930	

from which

- A fir, 14" dia., bears N.30°E., 46 lks., mkd: T29S R4E S4  
BT.
- A fir, 10" dia., bears S.81°E., 63 lks., mkd: T29S R4E S9  
BT.
- A fir, 12" dia., bears S.16°W., 69 lks., mkd: T29S R4E S8  
BT.
- A fir, 9" dia., bears N.43°W., 34 lks., mkd: T29S R4E S5  
BT.