

TOWNSHIP 29 RANGE 04E POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33; & 4 T30-4E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, US Cadastral Engineer, Under Special Instr. dated Aug. 24, 1928, Group No. 133; surveyed Oct. 1928/July 1929 - (DCSO records C.S. File 65/87-42(F))

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 S33
S 4
1929

from which

A hemlock, 12" dia., bears S.75½°E., 73 lks., mkd: 1/4 S4 BT
A fir, 10" dia., bears N.70°W., 58 lks., mkd: 1/4 S33 BT.

Jackson Co. Surveyors Office, Edward McGinty, Co. Surveyor - B. Malotte & R. Frost - Aug. 9, 1978 - C.S. File 58/183-10

Found - Projecting 9", the 1" dia. iron pipe with GLO brass cap (properly) mkd:

Orig. BTs recorded by Raymond in 1929 fd as follows:
Hemlock, 22" dia., with healed single blaze, brs S.75½°E., 47.85 ft. to center. Record; S.75½°E., 48.18 ft.

Fir snag, 15" dia., with healed single blaze, brs N.71½°W., 37.93 ft. to center. Record; N.70°W., 38.28 ft.

New tree CS-BT -

White pine, 14" dia., brs N.64½°W., 9.62 ft. to center of tree at lower blaze.

Corner lies about. 300 ft. West of location marker on 8" dia. White pine located approximately 50 ft. West of road.
V=18½°