

TOWNSHIP 29 RANGE 04E POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Cor. Secs. 33, 34; 3 & 4 T30-4E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, US Cadastral Engineer, Under Special Instr. dated Aug. 24, 1928, Group No. 133; surveyed Oct. 1928/July 1929 - (DCSO records C.S. File 65/87-42(F))

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 3, 4, 33, & 34, with brass cap mkd:

T29S R4E  
S33|S34  
S 4|S 3  
T30S  
1929

from which

- A fir, 9" dia. bears N.34°E., 15 lks. mkd: T29S R4E S34 BT
- A fir, 18" dia. bears S.11½°E., 62 lks mkd: T30S R4E S3 BT
- A fir, 22" dia. bears S.56°W., 25 lks. mkd: T30S R4E S4 BT
- A fir, 14" dia., bears N.19½°W., 26 lks., mkd: T29S R4E S33 BT.

Jackson Co. Surveyors Office, Edward McGinty, Co. Surveyor - J. Swanson & R. Frost - 8/7/1978 - C.S. File 58/183-7

-----  
Found - Orig. Monument not fd.  
Orig. BTs recorded by Raymond in 1929 fd as follows:  
Fir snag, 14" dia., with healed single blaze, brs record; N.34°E., 9.90 ft. to center.

SE BT now gone.  
Shasta red fir, 24" dia., containing scribe mkd in partially exposed single face, brs S.56°W., 16.11 ft. to center. Record; S.56°W., 16.50 ft.  
Douglas fir, 23" dia. with healed single blaze, brs N.19½°W., 17.77 ft. to center. Record; N.19½°W., 17.16 ft.

New - From the (FD) evidence, at the location described below, I set a 1x36" G.I. pipe, with a 2½" bronze disc mkd:

JACKSON COUNTY 1978  
T29S R4E  
33|34  
4|3  
1930

I mound stones around corner & mrk a new tree CS-BT: Hemlock, 6" dia., brs S.21°W., 25.43 ft. to center of tree at lower blaze.

NOTE - No trees available in NE quadrant.  
Corner lies about 40 ft. South of road, C E-W.  
V=17°