

TOWNSHIP 29 RANGE 04E POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records Vol. 26 page(s) 10916)

-----  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for cor. of secs. 15, 16, 21, & 22, with brass cap mkd:

T29S	R4E
S 16	S 15
S 21	S 22
1930	

from which

- A pine, 8" dia., bears N.42°E., 83 lks., mkd: T29S R4E S15 BT.
- A pine, 10" dia., bears S.44°E., 45 lks., mkd: T29S R4E S22 BT.
- A pine, 10" dia., bears S.68°W., 5 lks., mkd: T29S R4E S21 BT.
- A pine, 10" dia., bears N.55°W., 25 lks., mkd: T29S R4E S16 BT.