

TOWNSHIP 29 RANGE 04E POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Secs. 34; & 3 T30-4E

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Herbert N Raymond, US Cadastral Engineer, Under Special Instr. dated Aug. 24, 1928, Group No. 133; surveyed Oct. 1928/July 1929 - (DCSO records C.S. File 65/87-42(G))

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S34}{S3}$
1929

from which

A fir, 10" dia., bears S.58°E., 23 lks., mkd: 1/4 S3 BT.

A pine, 12" dia., bears N.35°E., 32 lks., mkd: 1/4 S34 BT.

Jackson Co. Surveyors Office, Edward McGinty, Co. Surveyor - J Swanson & R Frost - 8/7/1978 - C.S. File 58/183-9

Found - Projecting 3" the 1" dia. iron pipe with GLO brass cap (properly) mkd.

Orig. BTs fd as follows:

Pine snag, 14" dia., containing scribe mkd in partially exposed face, brs N.35°E., 21.25 ft. to center. Record; N.35°E., 21.12 ft.

W.Fir, 16" dia., with healed blazes, brs S.58°E., 14.84 ft. to center. Record; S.58°E., 15.18 ft.

New - Mark new trees CS BT and take measurements to center of trees at lower blaze:

Hemlock, 14" dia., bears N.88°E., 28.48 ft.

White fir, 22" dia., brs S.86°W., 18.29 ft.

V=19 1/4°