

TOWNSHIP 29 RANGE 04E POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Cor. Secs. 34, 35; 2, & 3 T30-4E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, US Cadastral Engineer, Under Special Instr. dated Aug. 24, 1928, Group No. 133; surveyed Oct. 1928/July 1929 - (DCSO records C.S. File 65/87-42(G))

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 2, 3, 34, & 35, with brass cap mkd:

T29S R4E  
S34|S35  
S 3|S 2  
T30S  
1929

from which

- A fir, 10" dia., bears N.74½°E., 95 lks., mkd: T29S R4E S35 BT.
- A fir, 16" dia., bears S.27°E., 39 lks., mkd: T30S R4E S2 BT.
- A fir, 11" dia., bears S.56°W., 71 lks., mkd: T30S R4E S3 BT.
- A pine, 16" dia., bears N.57°W., 58 lks., mkd: T29S R4E S34 BT.

Jackson Co. Surveyors Office, Edward McGinty, Co. Surveyor - J Swanson & R. Frost - 8/7/1978 - C.S. File 65/87-8

-----  
Found - Bent over, the orig 2x36" iron pipe with attached GLO brass cap (properly) mkd:

I remove, straighten and replace the BC, in the orig. position, 26" in the ground, from which:

D.Fir, 24" dia., with healed blazes, brs S.27°E., 25.64 ft. to center. Record; S.27°E., 25.74 ft.

D.Fir, 17" dia., with healed single blaze, brs S.56°W., 46.32 ft. to center. Record; S.56°W., 46.86 ft.

Pine snag, 22" dia. containing scribe marks including "4" and "34 BT" in partly exposed face, brs N.57°W., 37.88 ft to center. Record; N.57°W., 38.28 ft.

NE BT now gone.

I mound stones around corner, mk the following trees CS BT and take measurements to center of trees at lower blaze:

W.Fir, 13" dia., brs N.42°E., 147.1 ft.

Shasta red fir, 25" dia., brs N.83°W., 43.0 ft. to center.

Corner lies approximately 85 ft. S.6°E., from location marker on 25" dia. fir, alongside road. V=20°