

TOWNSHIP 29 RANGE 04E POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records Vol. 26 page(s) 10899)

-----  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for cor. of secs. 26, 27, 34, & 35, with brass cap mkd:

T29S|R4E  
S 27|S 26  
S 34|S 35  
1930

from which

- A fir, 9" dia., bears N.81½°E., 59 lks., mkd: T29S R4E S26  
BT.
- A fir, 22" dia., bears S.64°E., 38 lks., mkd: T29S R4E S35  
BT.
- A fir, 6" dia., bears S.43°W., 14 lks., mkd: T29S R4E S34  
BT.
- A fir, 10" dia., bears N.71°W., 50 lks., mkd: T29S R4E S27  
BT.