

TOWNSHIP 29 RANGE 04E POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35; & 2 T30-4E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Herbert N Raymond, US Cadastral Engineer, Under Special Instr. dated Aug. 24, 1928, Group No. 133; surveyed Oct. 1928/July 1929 - (DCSO records C.S. File 65/87-42(H))

-----  
Set an iron post, 3 ft. long, 1" dia., 32" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  $\frac{S35}{S2}$   
1929

from which

- A fir, 16" dia., bears N.18°E., 53 lks., mkd: 1/4 S35 BT.
- A fir, 16" dia., bears S.83°E., 52 lks., mkd: 1/4 S2 BT.

Jackson Co. Surveyors Office, Edward McGinty, Co. Surveyor - J Swanson & R. Frost - 8/7/1978 - C.S. File 65/87-8

-----  
Found - 2" deep, the 1" dia. iron pipe with standard GLO brass cap (properly) mkd:

Orig. BTs fd as follows:

Shasta red fir, 25" dia. with healed single blaze  
brs N.18°E., 34.66 ft. to center. Record;  
N.18°E., 34.98 ft.

The NW branch, 20" dia. of a double fir, sawed stumps, brs S.83°E., 34.5 ft. to center. Record;  
S.83°E., 34.32 ft.

I mound stones around corner & mk a new tree CS BT:  
Shasta red fir, 24" dia., brs S.29°W., 36.64 ft. to center of tree at lower blaze.

Corner lies about 225 ft. South of location marker on 10" dia. fir (mkd with axed "X") alongside road.

V=18 1/2