

PRIMARY CORNER DESCRIPTION Cor. Secs. 35, 36; 1, & 2 T30-4E

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Herbert N Raymond, US Cadastral Engineer, Under Special Instr. dated Aug. 24, 1928, Group No. 133; surveyed Oct. 1928/July 1929 - (DCSO records C.S. File 65/87-42(H&I))

Set an iron post, 3 ft. long, 2" dia., 20" in the ground, to bed rock, raise a mound of stone, 3 ft. base, 1 ft. high, around the post, for cor. of secs. 1, 2, 35, & 36, with brass cap mkd:

T29S R4E
S35|S36
S 2|S 1
T30S
1929

from which

- A larch, 9" dia., bears N.34°E., 74 lks., mkd: T29S R4E S36 BT.
- A pine, 12" dia., bears S.48½°E., 50 lks., mkd: T30S R4E S1 BT.
- A pine, 9" dia., bears S.2°W., 36 lks., mkd: T30S R4E S2 BT.
- A fir, 6" dia., bears N.38½°W., 34 lks., mkd: T29S R4E S35 BT.

Jackson Co. Surveyors Office, Edward McGinty, Co. Surveyor - B. Malotte & R. Frost - Aug. 5, 1978 - C.S. File 58/183-10

Found - Projecting 8" in mound of stone, the orig. 2" dia IP with standard GLO brass cap (properly) mkd.

- Original bearing trees fd as follows:
- The stump of a down 9" dia. fir, scribed as recorded, brs N.34°E., 48.6 ft. to center. Record; N.34°E., 48.84 ft.
 - White pine, 18" dia., with scribe mkd visible in partly healed blaze, brs S.48½°E., 33.25 ft. to center. Record; S.48½°E., 33.0 ft.
 - The stump and base of a down lodge pole pine 9" dia. scribed as recorded, brs S.2°W., 23.0 ft. to center. Record; S.2°W., 23.76 ft.
 - Fir snag, 12" dia., with healed single blaze brs N.38½°W., 23.10 ft. to center. Record; N.38½°W., 22.44 ft.

New - I mk the following trees CS BT and take measurements to center of trees at lower blaze:

- Lodge pole pine, 5" dia., brs N.40½°E., 18.0 ft.
- White pine, 10" dia., brs S.6°W., 23.25 ft.
- Lodge pole pine, 15" dia., brs N.52°W., 40.80 ft.

V=19-3/4°