

TOWNSHIP 29 RANGE 04E POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 36; & 1 T30-4E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Herbert N Raymond, US Cadastral Engineer, Under Special Instr. dated Aug. 24, 1928, Group No. 133; surveyed Oct. 1928/July 1929 - (DCSO records C.S. File 65/87-42(I))

Set an iron post, 3 ft. long, 1" dia., 28" in the straighten, for ¼ sec. cor., with brass cap marked

¼ $\frac{S36}{S1}$
1929

from which

A fir, 10" dia., bears S.8°W., 41 lks., mkd: ¼ S1 BT.

A fir, 26" dia., bears N.23°W., 49 lks., mkd: ¼ S36 BT.

Jackson Co. Surveyors Office, Edward McGinty, Co. Surveyor - B. Malotte & R. Frost - 8/3/1978 - C.S. File 58/183-7

Found - The orig. 1x36" iron pipe with standard GLO brass cap (properly) mkd. lying horizontal, 6" below the surface of the ground

I straightened and re-set the BC, 26" in the ground in its original position.

Orig. BTs Raymond in 1929 fd as follows;

White fir, 14" dia., with healed single blaze, brs record; S.8°W., 27.06 ft. to center.

Shasta red fir, 38" diam. with healed single blaze, brs record; N.23°W., 32.34 ft. to center.

Corner lies in cat logged area, about 300 ft. East of location marker on 12" diam. fir, alongside road. V=18°

Jackson Co. Surveyors Office, Roger R. Roberts, Co. Surveyor - H. Durkee & B. Beeman - Aug. 13, 2008 - C.S. File 65/87-41

Found - At the corner position, exposed 8", the 1" dia. galv. iron pipe with a 2½" brass cap set by the GLO in 1929, (properly) marked:

Orig BTs recorded by the GLO in 1929, fd with healed blazes & measured to center of trees at base:

Fir snag brs. record; S.8°W., 27.1 ft.

Shasta fir, now 43" dia. brs. rec; N.23°W., 32.3 ft.

New - Mark new BTs "CS" "BT" and take measurements to center of trees at lower blaze:

Shasta fir 10" dia. brs. S.50¾°W., 13.2 ft.

Shasta fir 6" dia. brs. N.39¼°E., 9.2 ft.

W. fir 9" dia. brs. S.25°E., 25.1 ft.

Corner lies approx. 300 ft. east of spur road.
V=15°45'