

TOWNSHIP 29 RANGE 04E POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 36; 30 & 31 T29-5E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records Vol. 25 page(s) 10871-2)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 25, 30, 31, & 36, with brass cap mkd:

T29S  
R4E|R5E  
S 25|S 30  
S 36|S 31  
1930

from which

- A fir, 22" dia., bears N.68°E., 51 lks., mkd: T29S R5E S30  
BT.
- A fir, 24" dia., bears S.18°E., 20 lks., mkd: T29S R5E S31  
BT.
- A fir, 20" dia., bears S.44°W., 37 lks., mkd: T29S R4E S36  
BT.
- A fir, 18" dia., bears N.54°W., 79 lks., mkd: T29S R4E S25  
BT.