

TOWNSHIP 29 RANGE 04E POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 12; 6 & 7 T29-5E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records Vol. 25 page(s) 10877)

-----

Set an iron post, 3 ft. long, 2" dia., 22" in the ground, to rock, and build a mound of stone, 3 ft. base, 1 ft. high, around the post, for cor. of secs. 1, 6, 7, & 12, with brass cap mkd:

T29S  
R4E|R5E  
S 1 | S 6  
S12|S 7  
1930

from which

- A pine, 26" dia., bears N.48°E., 30 lks., mkd: T29S R5E S6 BT.
- A fir, 15" dia., bears S.19°E., 23 lks., mkd: T29S R5E S7 BT.
- A pine, 5" dia., bears S.24°W., 4 lks., mkd: T29S R4E S12 BT.
- A larch, 10" dia., bears N.16°W., 38 lks., mkd: T29S R4E S1 BT.