

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 038030

PRIMARY CORNER DESCRIPTION SW cor. Benj. L. Stephen DLC #38

Alias 039060 Description SE cor. Hans Weaver DLC #39

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,
dated June 8, 1857

The SW cor. which is a Fir, 12" dia., from which
A Fir 30" dia., bears N.30°W., 27 lks.
A Fir 10" dia., bears N.65°E., 58 lks.

A. Boyer, Deputy Co. Surveyor - Wit: P.R. Weaver; Mrs. A.S.
Fetteman; Delbert Trask and Ted Shellabarger - Oct. 12, 1938
- C.S. File 16/4 and M 3-67

Set from evidence furnished by P.R. Weaver and from remains
of old fence, no evidence, except stump holes of original
bearing trees remains. Marked:

An 8" Fir N.33°E., 95.0 ft.

A 6" Fir N.86°W., 31.5 ft.

Drove a 3/4" steel drive shaft for corner on E. and W. fence
line.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike
Darby; Wm Stoffel crew - April 1963 - C.S. File 52/126-113

Found - Geared axle at corner and NE. BT, now dead.
NW BT not found.

Fences run East, West and North from corner.

New BTs -5" R.Fir bears N.76°E., 42.1 ft. scribed SW DLC 38
CS BT.

11" R.Fir bears N.41°W., 52.5 ft. scribed SE DLC 39
CS BT.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral
Surveyors under Group #'s 255; 701; 938 - Surveyed July
1967/Oct 1977 (DCSO records Vol. 39 Page(s) 15896)

The SW. cor. of DLC #38, identical with the SE. cor. Claim
#39, perpetuated and recorded by Boyer in 1938, from evidence
no longer in existence, monumented with an axle, 3/4" dia.,
firmly set, projecting 3" above ground. This corner is
accepted as the best available evidence of the original
corner position, from which the remains of bearing trees mkd.
by Byron in 1963:

A Red Fir snag 6" dia., bears N.62½°E., 64 lks. dist.,
with scribe marks SW DLC 38 CS BT visible on partially
healed double blaze.

A Fir 15" dia., bears N.42¼°W., 80½ lks. dist., with
healed double blaze.

At the corner point

(Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 038030

PRIMARY CORNER DESCRIPTION SW Cor. Benj. L. Stephens DLC #38

Alias 039060 Description SE Cor. Hans Weaver DLC #39
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,
directly over inverted axle, with brass cap mkd:

T 29 S R 4 W
C 39 | C 38
S 21
1969

from which a new bearing tree

A Fir 12" dia., bears N.85°E., 102 lks. dist. mkd. SW DLC
38 BT.

Corner is located in cor. of wire fences, with fences
extending N., E., and W.

Found OK by D. Beedle, April 2001 - M138-9
Fd. OK by D. Beedle, May 2004- M144-55
Fd. Ok by W. Ruppert, May 2005, 2005-0074A&B