

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy, dated June 8, 1857

-----

Set a post interior cor., from which  
 An Oak 9" dia., bears N.2°W., 160 lks.  
 A Laurel 18" dia., bears N.45°E., 80 lks.  
 A Pine 36" dia., bears S.88°W., 84 lks.

W.H. Wood, Deputy Co. Surveyor - Wit: W.S. Crear and A.C. Redifer - Nov. 3-6, 1925 - Vol. 3 Pg. 229

-----

Set Iron pipe. Stump of BT, S.88°W., 84 lks. checks.  
 Tie to section corner 16, 17, 20 and 21, checks.  
 No trees near.

Fd. OK, Aug. 1993 by Bruce Shaner - RM 3-79

Douglas County Surveyors Office - Randall Smith & Stephen Flause - Sept. 8, 1993 -C.S. 64/46-14

-----

Found - 1" I.D. Iron pipe with 2" dia. coupling protruding 2" above ground.

No evidence of Original BTs found.

From orig. DLC field notes the section corner of 16,17,20, & 21 was noted as being north 7 chs. & West 5.25 chs. from DLC cor. (N.36°52'17"W., 577.5); Rm 3-79 by Bruce Shaner RLS 430 has a calculated tie on map of N.36°55'28"W., 582.8 ft.

Monument set: Position of iron pipe is referenced. I.P. measured 12" long. A 2 3/8" dia. DCSO brass cap on a 1 3/8" dia. by 32" long I.P. is set at referenced position. BC/IP protrudes 6" above ground. I.P. is set along North edge of DCSO BC/IP, protrudes 3" above ground. Cap mkd.

Douglas County Surveyors Office  
T29S R4W

|NW  
Int
DLC 39 1993

New BTs -17" dia., J.Pine double blazed and scribed "NW INT DLC 39 CS BT" bears N.45½°E., 14.6 ft.

13" dia., double trunked madrone double blazed & scribed "NW INT DLC 39 CS BT" on East trunk, root crown bears West 23.2 ft.

4" dia., W.Fir double blazed & scribed "X BT" bears N4½°E., 48.1 ft.

27" dia., J.Pine double blazed & scribed "NW INT DLC 39 CS BT" bears N.9°W., 30.8 ft.

Corner lies at the intersection of old mostly down fences

running north and west. \_\_\_\_\_