

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 30; 24 & 25 T29-5

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - James E. Freeman, under Contract #1 dated May 28, 1851 (DCSO records, Vol. 15 Page 6353)

Set post, cor. of Secs. 19, 24, 25, & 30, (in creek) from which

- A Maple, 16" dia., bears N.50°W., 65 lks.
- A Maple, 8" dia., bears S.26°W., 70 lks.
- A Maple, 24" dia., bears N.3°E., 107 lks.
- An Alder, 15" dia., bears S.88°E., 28 lks.

B.L.M. Survey By Irving Zirpel, Jr., under Group #355. Surveyed July/Sept. 1957 (DCSO records Vol. 28 Page 12109)

Point for the cor. of secs. 19, 24, 25, & 30, at proportionate distance; there is no remaining evidence of the orig. corner. Point for cor. falls on the right bank of South Myrtle Creek.

Set an iron post, 30" long, 2" dia., 28" in the ground in bed rock of the stream bottom, and in a mound of stone, 3' base, 1' high, with brass cap marked

T 29 S
R 5 W * R 4 W
S 24 * S 19
S 25 * S 30
1957

from which

- A Maple, 8" dia., bears N.14°E., 231 lks. dist., mkd. T29S R4W S19 BT
- A cottonwood, 16" dia., bears S.28½°E., 160 lks. dist., mkd. T29S R4W S30 BT
- A cottonwood, 20" dia., bears S.43 3/4°W., 223 lks. dist., mkd T29S R5W S25 BT
- A Cedar, 11" dia., bears N.21°W., 143 lks. dist., mkd. T29S R5W S24 BT

B.L.M. Survey By Boyd W. Peterson, under Group #1394. Surveyed Aug. 1987/Jan.1988 (DCSO records Vol. 48 Page 18511)

The cor. of secs. 19, 24 25, & 30 on the W. bdy. of the Tp. determined at record dist. from the remaining bearing trees mkd. by Zirpel:

- A cottonwood, 20" dia., bears S. 53 3/4° W., 223 lks. dist., with healed blaze. (Record, S.43 3/4°W.)
- A Cedar, 22" dia., bears N.23°W., 143 lks. dist., with healed blaze. (Record, N.21°W.)

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 14" in the ground, in a mound of stone, 3' base, to top, with brass cap mkd. (Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 30; 24 & 25 T29-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T 29 S
R 5 W * R 4 W
S 24 * S 19
S 25 * S 30
1987

from which new bearing trees
A Maple, 22" dia., bears N.5 3/4°E., 201 lks. dist., mkd.
T29S R4W S19 BT
A Maple, 14" dia., bears S.26°E., 179 lks. dist., mkd.
T29S R4W S30 BT
Deposit white "DEEP-1" magnetic marker at base of stainless
steel post.
Corner is located on the N. bank of South Myrtle Creek.

Fd. Ok by K.DeGroot, July 1997 - M124-60
Fd. OK by K.DeGroot, Aug. 1998 - M129-11

Kris DeGroot - For: Silver Butte Timber Co. - Aug. 2013 -
M157-80

Fd. BC & accessories.
Geodetic coordinates:
Lat: 43°01'36.854799"N Long: 123°13'36.871441"W

2