

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec Cor 7, 18; 12 & 13 T29-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - James E. Freeman, under Contract #1 dated May 28, 1851 (DCSO records, Vol. 15 Page 6352)

Set post cor. of Secs. 7, 12, 13, & 18, from which
A Laurel, 9" dia., bears N.68°W., 17 lks.
A W. Oak, 9" dia., bears S.68°W., 23 lks.
A W. Oak, 11" dia., bears S.5°E., 30 lks.
A B. Oak, 12" dia., bears N.39°E., 52 lks.

G.L.O. Survey by W.F. Briggs, Under Special Instructions, dated Jan. 18, 1899. (DCSO records Vol. 15 Page 6416)

Post gone W. trees standing.
Re-establish cor. in the original position by setting a post 4' long, 4" sq. 24" in the ground, mkd:
T29S S7 on NE, R4W S18 on SE, R5W S13 on SW, T29S S12 on NW faces;
with 4 notches on S., and 2 notches on N. edges, from which original BTs
B. Oak, 12", bears N.39°E., 52 lks.
W. Oak, 9", bears S.68°W., 23 lks.
W. Oak, 11", bears S.5°E., 30 lks.
Laurel, 9", bears N.68°W., 17 lks.

John H. Markham, Jr., - Witness: George Vaughn - Aug. 30, 1951 - C.S. File 40/3752

Fnd - A dead W. Oak snag 11" dia., bears S.5°E., 20.0', old scribe showing (R4W, T29S, S18).
A Laurel Stump 12" dia., bears N.68°W., 11.0', OBT.
AT corner point I set a 1"x30" Iron Pipe, from which:
A Laurel 36" dia., bears S.85°W., 27.0', mkd: S13, T29S, R5W, BT.
A Fir 10" dia., bears N.64°W., 31.0', mkd: S12 BT.
A Fir 20" dia., bears N.38°E., 9.5', mkd: S7 BT, bark scribe)
A Fir 10" dia., bears S.40°E., 25.5', mkd: S18 BT.
There is an old fence running E. & W. from the corner.

A. R. Evans - For: L.K. Snyder - Witnesses: G. E. Johnson, M.E. Evans, J.I. Clinton - Apr. 10, 1953 - C.S. File 41/247-2

Found - 1" iron pipe and 2 orig. BTs.
10" B. Oak, S.5°E., 30 lks.
9" B. Oak, S.68°W., 23 lks.
(Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec Cor 7, 18; 12 & 13 T29-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New BTs -30" Madrone N.81°W., 28.2', mkd: T29-R5 S12-BT
RE 2741.
22" Fir, N.30°E., 11.4', mkd: T29-R4, S7.

Doug. County Surveyors Office - James. W. Byron, Deputy -
Dale McFarland and John Powell - March 1962 - C.S. 49/64-78

Found - 1" I.P. at cor. & BTs, bark scribed, as recorded
by Evans, 1953.
I rescribe 22" R. Fir N.30°E., 11.4', S7 T29S R4W CS BT.
New BTs -12" R. Fir bears S.37°E., 25.3', scribed S18 CS BT.
14" R. Fir bears S.29°W., 44.0', scribed S13 T29S
R5W CS BT.
Note - Corner under E.W. Fence.

Found OK By D. Bentz 11/87 - M 105-19

BLM dependent resurvey by Wayne L. Rogers, Dale T. Bedell,
Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning,
Surveying Technician, under Group #1625 surveyed Sept. 1991
thru April 1993 - (DCS0 records Vol. 52 Page(s) 19776-7)

From the cor. of secs. 7, 12, 13, & 18, perpetuated &
recorded by Markham, in 1951, from the remains of original
bearing trees no longer in existence, further perpetuated by
Evans, in 1953, further perpetuated by Byron, in 1962;
monumented with an iron pipe, 1" diam., firmly set,
projecting 6" above ground, from which the remains of the BTs
mkd. by Evans:

A sawed fir stump, 30" diam., bears N.32½°E., 17 lks.,
burned, no marks visible.

A madrone, 36" diam., bears N.86 3/4°W., 42 lks., burned,
no marks visible.

and the remains of a bearing tree mkd. by Byron

A burned fir, 17" diam., bears S.37½°E., 38 lks., with a
healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 25" in the
ground, with brass cap mkd.

T29S
R5W R4W
S 12 | S 7
S 13 | S 18
1992

There are no suitable trees available, this area was burned
in 1987.

Deposit a white "DEEP-1" magnetic marker at base and iron pipe
inside the stainless steel post.