

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7; & 12, T29-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - James E. Freeman, under Contract #1 dated May 28, 1851 (DCSO records, Vol. 15 Page 6351)

Set ¼ sec. post, from which
A B.Oak, 14" dia., bears N.33°W., 93 lks.
A B.Oak, 10" dia., bears South, 65 lks.

BLM dependent resurvey by Wayne L. Rogers, Dale T. Bedell, Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Surveying Technician, under Group #1625 surveyed Sept. 1991 thru April 1993 - (DCSO records Vol. 52 Page(s) 19777)

Point for the ¼ sec. cor. of secs. 7 & 12, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" diam., 23" in the ground, with brass cap mkd.

T29S
R5W R4W
¼
S 12 | S 7
1992

from which
A fir, 17" diam., bears N.57°E., 32 lks., mkd. ¼ S7 BT.
A fir, 12" diam., bears S.2°W., 36 lks., mkd. ¼ S12 BT.
Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

Kris DeGroot - 12/2010 - M157-36

Lat: 43°03'46.490798" N. Long: 123°13'34.994931" W.
Found a 1992 USBLM Stainless steel post with brass cap and accessories by W.Rogers per 1991-1993 USBLM dependant resurvey

James Klein - Michael Erickson - Douglas Popham - For: Williams/Pacific Connector Pipeline - 6/2015 - M166-38 A-D

Found - 3¼" Brass cap stamped BLM 1992
21.5" Fir with healed face & tag dated 4/92 N.57°E., 21.1'
16" Fir with healed face & tag dated 4/92 S.2°W., 23.8'