

PRIMARY CORNER DESCRIPTION NW Township Corner (NW Cor. Sec. 6)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - James E. Freeman, contract #1 dated May 28, 1851.
(DCSO records Vol. 13, Pg. 5603-5604)

Set post for Township Corner from which:

- A B.Oak, 16" dia. bears N.31°E., 38 lks. dist.
- A B.Oak, 11" dia. bears N.19°W., 25 lks. dist.
- A B.Oak, 18" dia. bears S.77½°E., 50 lks. dist.
- A B.Oak, 12" dia. bears S.46°W., 210 lks. dist.

West boundary of T.28-4, surveyed by W.H. Byars, contract #376 dated Jan. 22, 1881. (DCSO rec. Vol. 13 Pg. 5611-5612)

Set new post as per instructions, bearing trees standing viz:

- A B.Oak, 16" dia. bears N.31°E., 38 lks. dist.
- A B.Oak, 11" dia. bears N.19°W., 25 lks. dist.
- A B.Oak, 18" dia. bears S.77½°E., 50 lks. dist.
- A B.Oak, 12" dia. bears S.46°W., 210 lks. dist.

James W. Byron, Deputy County Surveyor - April-May 1957
C.S. File 47/180.

Found - 3 original BTs. I open N.E. BT and find good scribing. The N.W. BT gone-stump hole only.
I do not open S.W. or S.E. BTs-show old blazes and all check for bearings & distances.

Note- Corner 10 feet west of N-S fence.
Set an iron pipe with brass cap mkd:

	36	31	T28S	Co. Surveyors Office
	1	6		1957
R5W		R4W		
		T29S		

New BTs- 20" R.Fir, N.82°W., 10.8' mkd: T28S R5W S36 CSBT.
12" R.Fir, S.46°W., 54.2' mkd: T29S R5W S1 CSBT.
12" R.Fir, S.54°E. 50.4', mkd. T29S R4W S6 CSBT.
Reblaze and rescribe orig. 16" B.Oak, (now 24"dia.)
N.31°E., 25.1' mkd: T28S R4W S31 CSBT.

Fd. OK, Wm. Ruppert, Jan/March 1983, M 93-68

continued next page

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW Township Corner (NW Cor. Sec. 6)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Wayne L. Rogers, Dale T. Bedell, Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Surveying Technician, under Group #1625 surveyed Sept. 1991 thru April 1993 - (DCSO records Vol. 52 Page(s) 19780)

The cor. of Tps. 28 and 29 S., Rs. 4 and 5 W., perpetuated by Byron, Deputy County Surveyor, in 1957, bears N.0°18'30"E., 39.280 chs. dist.; monumented with an iron post, 1¼" diam., firmly set, projecting 10" above ground, with properly marked brass cap.

from which the remaining original bearing tree

An oak, 30" diam., bears N.31°E., 38 lks., with a healed double blaze.

and the remains of the bearing trees mkd. by Byron

A fir, 18" diam., bears S.55°E., 76 lks., with a healed double blaze.

A fir, 22" diam., bears S.46½°W., 82 lks., with a healed double blaze.

A fir stump, 30" diam., bears N.82°W., 16 lks., with a healed double blaze.

and a new bearing tree

A fir, 7" diam., bears N.15½°W., 51 lks., mkd. T28S R5W S36 BT.

DCSO-GIS Corner visitation - 4/15/2004 - Typed: 2/1/2011 - C.S. File 67/33-1

Monument - BC/IP - 1.25"
Comment - OK