

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 31 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6357)

-----  
Set ¼ sec. post at proper distance, from which  
A Laurel 5" dia., bears N.18°W., 35 lks. dist.  
A Laurel 6" dia., bears S.45°W., 27 lks. dist.

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 15 Page(s) 6408)

-----  
The locality of the ¼ sec. corner has been burnt over, destroying all traces.  
Set a Cedar post 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which  
A Fir 48" dia., bears N.32°W., 19 lks. dist. mkd. ¼ S BT.  
A Maple 8" dia., bears N.36°E., 74 lks. dist. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - Wit: George Vaughn; Dennis Vaughn - ~~Aug. 17, 1951~~ 7/18/1951 - C.S. File 40/304-2

-----  
Determined by O.B.T., a Fir 52" dia., bears N.32°W., 12.5 ft., scribe showing.  
At corner point, Set 1" x 30" Iron pipe, from which  
A Cedar 10" dia., bears N.1°E., 30.0 ft. mkd. ¼ S S31 BT  
A Maple 10" dia., bears N.80°W., 62.0 ft. mkd. ¼ S 2880 BT  
Tsp. corner bears S.76½°W., 700.0 ft.  
N. 1/4 Corner Sec. 6, T30-4, bears N.76°30'E., 2076.0 ft.

BLM dependent resurvey by Wayne L. Rogers, Dale T. Bedell, Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Surveying Technician, under Group #1625 surveyed Sept. 1991 thru April 1993 - (DCSO records Vol. 52 Page(s) 19770-1)

-----  
From the ¼ sec. cor. of sec. 31 only, on the S. bdy. of the Tp., perpetuated by Markham, in 1951, monumented with rust lined hole, 1¼" diam., with an iron pipe, 1¼" diam., 24" long, lying alongside, from which the remaining original BT:  
A fir, 56" diam., bears N.32°W., 19 lks. no marks visible. and a bearing tree mkd. by Markham  
A maple, 17" diam., bears N.80¼°W., 89 lks., with fragmentary scribe marks visible on opened blaze.  
At the corner point  
Set a stainless steel post, 28" long, 2½" diam., 26" in the ground, with brass cap mkd. T29S R4W  
¼ S 31  
1992  
from which a new bearing tree  
A fir, 6" diam., bears N.3½°E., 77½ lks., mkd 1/4 S31 BT.