

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - James E. Freeman, under Contract #1 dated May 28, 1851 (DCSO records, Vol. 15 Page 6379)

-----  
Set 1/4 sec. post at proper dist., from which:  
A B.Oak, 24" dia., bears N.55°W., 14 lks.  
A B.Oak, 30" dia, bears S.15°W., 40 lks.

BLM dependent resurvey by Wayne L. Rogers, Dale T. Bedell, Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Surveying Technician, under Group #1625 surveyed Sept. 1991 thru April 1993 - (DCSO records Vol. 52 Page(s) 19794)

-----  
Point for the 1/4 sec. cor. of secs. 30 & 31, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2 1/2" diam., 27" in the ground, with brass cap mkd. T29S R4W

1/4 S 30  
S 31  
1992

from which

A fir, 17" diam., bears N.45 1/2°E., 4 lks., mkd. 1/4 S30 BT.

A fir, 11" diam., bears S.7 1/2°E., 17 1/2 lks., mkd. 1/4 S31 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

Kristian DeGroot - For: Roseburg Forest Products - July 1997 - M 124-60

-----  
Found - A 2 1/2" USBLM standard monument by Robert Browning, USBLM Cadastral Surveyor in 1992, firmly set, projecting 2" above the ground with a 3" dia, brass cap stamped: T29S R4W

1/4 S30  
S31  
1992

from which BTs by Browning in 1992:

A 20" D.Fir, N.45°30'E., 2.6', scribing visible.

A 14" D.Fir, S.7°30'W., 11.5', scribing visible.

Kris DeGroot - For: Silver Butte Timber Co. - Aug. 2013 - M157-80

-----  
Fd. BC & accessories.

Geodetic coordinates:

Lat: 43°01'36.336889"N

Long: 123°13'03.231330"W