

PRIMARY CORNER DESCRIPTION C 1/4 Cor. Sec. 30

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Kristian DeGroot - For: Roseburg Forest Products - July 1997
- M 124-60

Set - A 5/8"x30" Iron Rod flush with the ground with a 2"
dia., alum. cap stamped:

T29S R4W

C 1/4

!

S30

PLS 1941

from which:

A 9" D.Fir bears S.57°W., 22.4', scribed "C 1/4 S30 BT"

A 11" D.Fir bears S.24°W., 14.2', scribed "C 1/4 S30 BT"

A 5/8" Iron Rod w/pc "BTS Eng-Surv" bears N.57°E.,
20.0'.

A 5/8" Iron Rod w/pc "BTS Eng-Surv" bears N.24°W.,
20.0'.

All new BTs have a 6" red band painted around the tree, a
double blazed face painted red with a brass washer stamped
"PLS 1941" nailed into the lower blaze and a BT tag attached.
Bearings are taken to the center of the tree at the root
crown and distances are measured to a nail in the root crown
at the side and center of the tree.

Kris DeGroot - For: Silver Butte Timber Co. - Aug. 2013 -
M157-80

Set - A e"x30" iron rod 28" in the ground, with the M124-60
2" diam. alum. cap reset on the new iron rod and
stamped: T29S R4W C1/4 S30 1996 PLS1941 RESET 2013

From which a bearing trees per M124-60:

A 13" D.Fir bears S.80°15'W., 46.5 ft, with a healed
double blaze

A 15" D.Fir bears S.73°W., 37.1 ft, with a healed
double blaze faced towards the M124-60 corner
position. BT not retied.

New - A 15" D.Fir bears S.5°W., 21.2 ft, scribed "C 1/4 S30 BT"

A e"x30" iron rod bears N.47°10'26"E., 20.12 ft.
(M124-60 monument removed and reset)

A e"x30" iron rod bears N.44°28'19"W., 17.00 ft
(Utilized in the M124-60 position)

A e" iron rod per M124-60 bears N.86°49'33"W., 28.94
ft. I remove the alum. cap & replace with a plastic
cap.

Geodetic coordinates:

Lat: 43°01'10.061434"N

Long: 123°13'03.995113"W