TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 30

Alias Description
Alias Description
Alias Description
Alias Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6381)

Set ¼ sec. post at proper dist., from which
A B.Oak 24" dia., bears S.8°E., 100 lks. dist.
A B.Oak 10" dia., bears N.15°W., 125 lks. dist.

NF DCSO 10/1971 - C.S. File 49/67-47

BLM resurvey, by Boyd W. Peterson, under Group #1394 - Surveyed Aug. 1987/Jan. 1988 (DCSO records Vol. 48 Page(s) 18510-11)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an stainless steel post, 28" long, 2 1/2" dia., 28" in the ground, with brass cap mkd: T 29 S R 4 W

¼ S 19 / S 30
1987

from which
A Ponderosa Pine 29" dia., bears S.87¼°E., 110 lks. dist. mkd. ¼ S30 BT.
S W.Oak 12" dia., bears N.42¼°W., 96 lks. dist. mkd. ¼ S19 BT.
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
Corner is located in a pasture, S. of a woven wire fence 11½ lks. dist., which bears E. and W.

Kris DeGroot - For: Silver Butte Timber Co. - Aug. 2013 - M157-80

Fd. BC & accessories.
Geodetic Coordinates
Lat: 43°01'36.336889"N Long: 123°13'03.231330"W