

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 140340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor for Sec 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by William J. Ruppert - For: Allen, Coffey, Phillips,
Dame and Wilson - May 1976 - M 60-35

Set 5/8" Iron rod.

BLM resurvey by Boyd W. Peterson, under Group #1394, Surveyed
Aug. 1987/Jan. 1988 (DCSO records Vol. 48 Page(s) 18524)

The center 1/4 sec. cor. of sec. 19, established and recorded
by Ruppert in 1976, and is accepted as the corner, monumented
with an iron rod, 5/8" dia., firmly set, projecting 9" above
ground.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 22" in
the ground, directly over the iron rod, with brass cap mkd:

T 29 S R 4 W
C ¼
S 19
1987

from which

A Fir 4" dia., bears S.67 3/4°E., 13½ lks. dist. mkd. X BT

A Fir 6" dia., bears S.15°W., 28 lks. dist. mkd. C¼ S19 BT

Deposit white "DEEP-1" magnetic marker at base of stainless
steel post.

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates
Professional Land Surveyors - 2024 - M185-29 A/D

Found ok per record. Added paint, nails and BT tags to BTs.