

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey - Dennis Hathorn, Deputy, under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6383)

Set ¼ sec. post, from which
A Laurel 36" dia., bears N.7°W., 34 lks. dist.
A Laurel 15" dia., bears S.56°E., 36 lks. dist.

GLO survey by W.F. Briggs, Deputy Surveyor, under Special instructions, dated Jan. 18, 1899 - (DCSO records Vol. 15 Page(s) 6416)

¼ S. cor. post gone. Witness still in place.
Made new post in the original position, 3 ft. long, 3" sq., 24" in the ground mkd. ¼ S7 on N.; and S18 on S. face.

Ben B. Irving, County Surveyor - J. Byron; R. Irving; J. Fee, crew - March 1954 - C.S. File 45/234

¼ cor. set at midpoint on a line between sec. corners, 7, 8, 18 and 17 and 12, 7, 13 & 18.
Set brass cap mkd. "County Surveyors Office ¼ S7 - 18"
Blazed and scribed:
18" R.Fir "¼ S18 CS BT R4W", S.23°20'W., (48.3 ft.-24°10')= 44.1 ft.
20" R.Fir "¼ S7 CS BT R4W" N.85°20'W., 29.1 ft. 29.1 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm Stoffel crew - April 1963 - C.S. File 52/126-114

Found - Brass cap at corner and both BTs, now stumps, as recorded by Irving.
We now find orig. 36" now 48" Laurel snag, N.7°W., 22.4 ft. Open this BT and find good scribing "B".
Original SE. BT not found.
Remove brass cap from 1954 location and RESET to true corner. True corner bears N.80°W., 13.0 ft. from original position of brass cap.
New BTs -4" Laurel bears S.55°E., 93.0 ft. scribed ¼ S18 CSBT
10" R.Fir bears N.43°E., 29.0 ft. scribed ¼ S7 CSBT.

Fd. OK, Nov. 1987 by D. Bentz - M 105-19

Corner Fd. and tied in BLM resurvey by Boyd W. Peterson, under Group #1394, surveyed Aug. 1987/Jan. 1988 - (DCSO records Vol. 48 Page(s) 18519)

Fd. Ok by D.Edwards, 10/96, M 126-12.

continued next page

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. & used on BLM dependent resurvey by Wayne L. Rogers, Dale T. Bedell, Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Surveying Technician, under Group #1625 surveyed Sept. 1991 thru April 1993 - (DCSO records Vol. 52 Page(s) 19770)

Fd. 4/2015 by N. Hibbs, 2015-0009A&B

Brent Knapp - For: Lone Rock Timber Co. - 11/2022 - M181-51

Found - Brass cap per record.
10" Madrone, S.55°E., 93.0', healed scar & tag.
23" R.Fir, N.43°E., 29.0', healed scar & tag.
Set - 7" Madrone, S.26°W., 8.9', scribed "¼ S18 BT"
6" Madrone, N.32°W., 10.2', scribed "¼ S7 BT"