

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73 dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6387)

Set ¼ sec. post, from which
A Fir 10" dia., bears S.60°W., 25 lks. dist.
A Laurel 12" dia., bears N.10°W., 56 lks. dist.

Survey by Robert M. Thompson - Wit: L. Washburn, Jr. and H. Hubbard - For: Patrick Lumber Co. - June 5, 1958, Filed, Dec. 22, 1958 - C.S. File 41/62

Found - 10" Fir S.60°W., 16.5 ft., now 26" stump, chopped open long butt, I find "¼S" scribed.
Other BTs burnt out, stump hole evident.
To renew, I SET 1/2" Iron pipe, scribed new BTs:
20" Madrona S.40°20'E., 17.8 ft.
12" Madrona N.5°E., 21.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm Stoffel crew - April 1963 - C.S. File 52/126-116

Found - 1/2" I.Pipe as corner and both BTs as recorded by Thompson, shows good scribing.
Set brass cap alongside 1/2" I.P. and mkd:
County Surveyors Office
T 29 S R 4 W
¼ $\frac{S}{S} \frac{6}{7}$
1963

No new BTs.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Wit: John Powell & Karen Reed - April 4, 1982 - C.S. File 61/30-21

Found - 1/2" I.P. set flush with the ground along the South edge of 1½" I.P. with 1963 properly mkd. brass cap. Cap is firmly set and protrudes 10" out of ground.
Orig. 10" Fir now 26" stump bears S.60°W., 17.2 ft. (Rec. 16.5 ft.). I find butt section of tree alongside stump with scribed "¼S" visible on an opened face. (this piece is rotting badly.)
20" now 27" Madrone with scribed "¼S / ~ (83 BT" visible in an unhealed blaze, bears S.40°E., 19.6 ft. (Rec. dist. of 17.8 ft. fits well to face.
12" now 14" Madrone now a windfall bears N.5°E., 21.0 ft. to root hole. Scribed "¼ S6 368 ∇" visible in unhealed blaze. (Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs -13" Fir scribed "¼ S7 CS BT" in double blaze bears S.7°W., 38.6 ft.
16" Fir scribed "¼ S6 CS BT" in double blaze bears N.83½°E., 21.5 ft.
14" Fir scribed "¼ S6 CS BT" in double blaze bears N.3°E., 8.4 ft.

Fd. & used on BLM dependent resurvey by Wayne L. Rogers, Dale T. Bedell, Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Surveying Technician, under Group #1625 surveyed Sept. 1991 thru April 1993 - (DCS0 records Vol. 52 Page(s) 19799-800)

David Edwards For: Roseburg Resources - June 2025 - M186-12
Found - 25" dead madrone bears S.27¾°E. 41.6 (Rec S.28°E. 41.0')
31" Fir w/healed blaze bears N.14½°W. 93.7' (Rec 93.3')
New - 11" Fir scribed "¼ SS BT" S.27¾°E. 27.6' bears S.27¾°E. 27.6'