

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 140640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM dependent resurvey by Wayne L. Rogers, Dale T. Bedell, Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Surveying Technician, under Group #1625 surveyed Sept. 1991 thru April 1993 - (DCS0 records Vol. 52 Page(s) 19801-2)

-----  
Point for the center ¼ sec. cor. of sec. 6, at intersection with the E. and W. centerline.

Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, with brass cap mkd.

T29S R4W  
C ¼ S 6  
1992

from which

A cedar, 12" diam., bears S.59°W., 105 lks. mkd. C ¼ S6 BT

A cedar, 6" diam., bears N.9°W., 68 lks., mkd. C ¼ S6 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, an iron pipe, 1" diam., firmly set, projecting 13" above ground, established by person(s) unknown, bears S.12°24'30"W., 0.205 chs. dist.

David Edwards For: Roseburg Resources - June 2025 - M186-12

Found - 20" Cedar w/healed blaze bears S.59°W. 69.3'

BLM Cedar N.9°W. 44.9' is down.

New - 10" Maple scribed "C ¼ S BT" N.62°W. 28.5'

5.5ft posts set 2' E. And 2' W. On line.