

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec Cor for 31 and 32 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New fence corner bears S.70°E., 8 ft.
This area clear cut. E-W log road 150 ft. North of corner.
New BT -24" Laurel S.58°W. 129.4 ft. scribed S6 T30SR4W CS BT

Found brass cap only, No BTs. by Glenn Baughman, July 1979 - M 78-30

Ronald Quimby - For: James Little - April 1999 - M 129-44

Found - County brass cap properly mkd., from which
A 10" Fir bears S.51°E., 29.0 ft., healed face.
A 12" Fir bears S.15½°W., 16.8 ft., marked "X BT"
A 16" Fir bears N.44½°W., 26.4 ft., healed face.
Note - BTs are from a 1994 BLM resurvey that has not been
filed as of the date of this survey.

BLM dependent resurvey by Wayne L. Rogers, Dale T. Bedell, Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Surveying Technician, under Group #1625 surveyed Sept. 1991 thru April 1993 - (DCS0 records Vol. 52 Page(s) 19790-1)

From the cor. of secs. 31 & 32, on the S. bdy. of the Tp., perpetuated by Barnhart, in 1947, from original evidence no longer in existence, further perpetuated by Byron, Deputy County Surveyor, in 1961, monumented with an iron post, 1¼" diam., firmly set, projecting 14" above ground, with properly marked brass cap.
from which the remains of the bearing trees mkd. by Barnhart
A fir snag, 10" diam., bears S.52½°E., 50½ lks., no marks visible.
A decayed fir stump, size indeterminate, bears N.22°W., 50 lks., with scribe marks T29S R W visible on open blaze.
and the remains of a bearing tree mkd. by Byron
A madrone snag, 23" diam., bears S.59°W., 196 lks., with healed upper blaze and scribe marks BT visible on partially healed lower blaze.
and new bearing trees
A fir, 4" diam. bears S.51°E., 44 lks. mkd. T30S R4W S6 BT
A fir, 5" diam., bears S.15½°W., 25½ lks., mkd. X BT.
A fir, 10" diam., bears N.44½°W., 40 lks., mkd. T29S R4W S31 BT.
From this point, the ¼ sec. cor. of sec. 31 only bears S.76°24'30"W., 42.145 chs. dist.

continued next page

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 and 32 only (South)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

David Edwards - For: Seneca Jones Timber Co. & Roseburg Resources Co. - 6/2010 - M 160-68

Found - Brass cap
11" Fir S.51°E., 29.0 ft.
10" Fir S.15½°W., 16.8 ft.
15" Fir N.44½°W., 26.40 ft.
All with healed blaze.

Fd. BC, 4/2018 - By D. Edwards, M174-36