

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec Cor for 29, 30, 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6378)

Set a post cor. secs. 29, 30, 31 and 32, from which
A Red Fir 24" dia., bears S.5°W., 23 lks. dist.
A Red Fir 16" dia., bears N.75°E., 19 lks. dist.
A Dogwood 4" dia., bears N.66°E., 62 lks. dist.
A Maple 4" dia., bears S.87°E., 35 lks. dist.

G.A. Barnhart, Surveyor - Wit: Weber and Stubblefield - Dec. 1946 - C.S. File 40/19A

Found 18" Red Fir BT, dead, measured N.5°E., 23 lks.
Set 3/4" iron rod 30" long for sec. cor. from which new BTs were set:
A 9" Fir bears N.19°52'W., 4.0 ft. dist.
A 5" Fir bears N.45°07'E., 20.3 ft. dist.
A 5" Yew bears S.64°57'E., 28.7 ft. dist.
A 16" Cedar bears S.50°03'W., 20.5 ft. dist.

Jack L. Sheppard, LS #180 - For: Umpqua Plywood - C.S. File 41/337 - M 3-68

Found - 3/4" Iron rod as set by Barnhart in 1946.
8" Fir N.19°52'W., 4.0 ft.
16" Cedar S.50°03'W., 20.5 ft.
Other 2 BTs destroyed by logging road.
Marked - 10" Soft Maple S.37°E., 51.9 ft. S32 LS 180 BT.
12" Cedar N.47°E., 44.3 ft. S29 LS 180 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm Stoffel crew - April 1963 - C.S. File 52/126-108

Found all BTs and 3/4" I.Rod at corner. NW. BT now down.
New BT - 12" R.Fir N.67°W. 22.9 ft. scribed S30 T29S R4W CS BT

BLM dependent resurvey by Wayne L. Rogers, Dale T. Bedell, Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Surveying Technician, under Group #1625 surveyed Sept. 1991 thru April 1993 - (DCSO records Vol. 52 Page(s) 19792-3)

The cor. of secs. 29, 30, 31, & 32, perpetuated by Barnhart, in 1946, from the remains of original evidence no longer in existence, further perpetuated by Sheppard, in 1955, further perpetuated by Byron, Deputy County Surveyor, in 1963; monumented with an iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above ground, from which the remains of bearing trees mkd. by Barnhart: continued next page

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A cedar, 40" diam., bears S.51 3/4°W., 32 lks., with healed blaze.
A root hole, bears N.3°W., 6½ lks., with decayed and down fir alongside, 10" diam., no marks visible.
and bearing trees mkd. by Sheppard
A cedar, 30" diam., bears N.46¼°E., 68 lks., with a healed double blaze.
A maple, 15" diam., bears S.39½°E., 79 lks., with a healed blaze.
and a bearing tree mkd. by Byron
A fir, 19" diam., bears N.66¼°W., 35 lks., with a healed double blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, directly over iron rod, with brass cap mkd.

T29S	R4W
S 30	S 29
S 31	S 32

1993

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Fd. Ok by D. Edwards, March 2002 - M139-75
Fd as per M139-75, by David Edwards- 6/2010 - M 160-68

Kris DeGroot - For: Silver Butte Timber Co. - Aug. 2013 - M157-80

Fd. BC & accessories.
Geodetic coordinates:
Lat: 43°00'41.427984"N Long: 123°12'30.458156"W